

SHEARS



Jaw
Highly wear resistant
with Hardox



Cutter
Exclusive cutting
array to maximize
cutting force



Gap Adjuster(Patented)



Quick & easy adjusting
for precise cutting line

Speed-up Valve
Maximize working
cycle speed

SPECIFICATION

Model	Unit	SC250	SC300
Suitable Excavator	ton	25~35	28~36
Weight (Incl. Mounting Cap)	kg	1920	2980
Max./Mid./Min. Centrifugal Force	ton	320/150/85	500/210/105
Max. Operating Oil Flow	l/min	240	280
Max. Oil Pressure (Min. Setting Pressure)	bar/psi	350/5076 (300)/4351	350/5076 (300)/4351
Dimension L x W x H	mm	2390 x 1090 x 820	2775 x 1350 x 820
Dimension A x D	mm	565 x 500	675 x 580
Dimension B x C	mm	470 x 290	555 x 305
●	mm	60	65
I-beam	mm	330	360
H-beam	mm	240	260
—	mm	15	20

Above specifications are subject to change without prior notice for performance enhancement.



1

WORLD'S FIRST HYDRAULIC GAP
ADJUSTER (PATENTED)

2

INCREASE WORKING SPEED WITH
SPEED-UP VALVE

3

UNIQUE CUTTER ARRAY FOR ENHANC-
ING CUTTING FORCE

4

EASY DETACHABLE COVER FOR MAIN-
TENANCE

5

360-DEGREE ROTATION