

VIBRO HAMMERR



Motor

Piston motor with high efficiency



Bearing

Customized design
completely resistible
under high vibration force



Vibration-Proof Rubber

Improve durability with
vibro-isolating rubber



Jaw

Tight clamping and easy moving

1

WIDE RANGE OF CONSTRUCTION
AREAS

2

ROTATING MOUNTING BRACKET

3

QUICK HYDRAULIC INSTALLATION

4

INTUITIVE DESIGN

5

OPTIONAL EXTENSION BOOM

SPECIFICATION

Model	Unit	SW250	SW300	SW400
Suitable Excavator	ton	18~26	25~35	34~45
Frequency	bpm	2800~3500	2500~3500	2000~2700
Eccentric Moment	Nm/in lbs	66/584	80/708	100/885
Centrifugal Force	kN	450	500	550
Amplitude	mm	12	14	16
Max. Oil Pressure (Min. Setting Pressure)	bar/psi	350/5076 (300)/(4351)	350/5076 (300)/(4351)	350/5076 (300)/(4351)
Max. Oil Flow	l/min	200	240	280
Slewing	degree	360	360	360
Weight	kg	1550	1700	1800
Ext. Boom Weight (Incl. Mounting Cap)	kg	580	700	870
Clamp Width(A)	mm	65	65	65
Dimension (L x W x H)	mm	1840 x 1040 x 750	1900 x 1100 x 790	1920 x 1190 x 840

Above specifications are subject to change without prior notice for performance enhancement.

