



| Breaker | Bucket crusher | Crusher | Quick Coupler | Auger | Attachments |

Product Line



Breaker



Silent Type

Description	Unit	SSD 10S	SSD 20S	SSD 30S	SSD 40S	SSD 50S
Operating Weight	kg	100	134	148	186	304
Overall Length	mm	1,087	1,215	1,285	1,363	1,682
Operating Pressure	bar	80~100	100~120	100~120	110~130	140~160
Required Oil Flow	l/min	10~20	15~25	25~40	25~45	30~45
Impact Rate	bpm	700~1,200	700~1,200	550~1,000	500~900	500~800
Impact Energy	joule	180	254	286	447	620
Hose Diameter	inch	3/8	3/8	1/2	1/2	1/2
Tool Diameter	mm	36	45	53	60	68
Applicable Carrier	ton	0,8~2,5	1,2~3,0	2,5~4,5	3,0~5,5	4,0~7,0

※The above specifications are subject to change without prior notice for improvement.



Standard Type

Description	Unit	SSD 10	SSD 20	SSD 30	SSD 40	SSD 50
Operating Weight	kg	7C	87	106	178	272
Overall Length	mm	1,050	1,146	1,230	1,288	1,491
Operating Pressure	bar	80~100	100~120	100~120	110~130	140~160
Required Oil Flow	l/min	10~20	15~25	25~40	25~45	30~45
Impact Rate	bpm	700~1,200	700~1,200	550~1,000	500~900	500~800
Impact Energy	joule	180	254	286	447	620
Hose Diameter	inch	3/8	3/8	1/2	1/2	1/2
Tool Diameter	mm	36	45	53	60	68
Applicable Carrier	ton	0,8~2,5	1,2~3,0	2,5~4,5	3,0~5,5	4,0~7,0

※The above specifications are subject to change without prior notice for improvement.



SSD 70S	SSD 100S	SSD 140S	SSD 160S	SSD 200S	SSD 200VS	SSD 300S	SSD 400S	SSD 500S	SSD 800S
405	530	880	1,307	1,462	1,710	2,454	3,020	4,120	7,415
1,684	2,068	2,361	2,615	2,701	2,766	3,057	3,306	3,782	4,443
140~160	120~150	150~170	150~180	160~180	160~180	160~180	160~180	160~180	190~210
40~70	60~100	80~120	100~140	100~150	120~160	150~190	170~230	190~270	290~370
400~800	400~800	400~700	400~600	400~600	400~700	300~550	250~400	200~350	200~400
945	1,029	2,630	4,740	5,210	5,830	8,250	12,110	14,870	16,740
1/2	3/4	3/4	1	1	1	1 1/4	1 1/4	1 1/4	1 1/4
75	85	100	125	135	135	150	160	180	210
6~9	7~12	11~16	14~18	16~21	16~25	25~32	30~42	45~60	70~100



SSD 70	SSD 100	SSD 140	SSD 160	SSD 200	SSD 200V	SSD 300	SSD 400	SSD 500	SSD 800
384	508	872	1,255	1,455	1,668	2,380	2,960	4,064	7,251
1,613	2,115	2,387	2,621	2,757	2,775	3,062	3,265	3,854	4,385
140~160	120~150	150~170	150~180	160~180	160~180	160~180	160~180	160~180	190~210
40~70	60~100	80~120	100~140	100~150	120~160	150~190	170~230	190~270	290~370
400~800	400~800	400~700	400~600	400~600	400~700	300~550	250~400	200~350	200~400
945	1,029	2,630	4,740	5,210	5,830	8,250	12,110	14,870	16,740
1/2	3/4	3/4	1	1	1	1 1/4	1 1/4	1 1/4	1 1/4
75	85	100	125	135	135	150	160	180	210
6~9	7~12	11~16	14~18	16~21	16~25	25~32	30~42	45~60	70~100