



| Breaker | Bucket crusher | Crusher | Quick Coupler | Auger | Attachments |

Product Line



»»» Crusher



• Primary Crusher

Model	Unit	SDC 03V	SDC 05V	SDC 15V	SDC 20V	SDC 25V	SDC 30V	SDC 45V
Operating Weight	kg	290	520	1,000	1,400	1,950	2,680	5,000
Opening Width of Jaw	mm	0~450	0~500	0~800	0~880	0~980	0~1,120	0~1,400
Operating Pressure	bar	210	240	260	280	300	320	320
Applicable Carrier	ton	2~3	5~7	13~18	20~22	22~25	28~37	35~48

※The above specifications are subject to change without prior notice for improvement.

• Secondary Crusher

Model	Unit	SDP 15V	SDP 20V	SDP 25V	SDP 30V	SDP 50V
Operating Weight	kg	890	1,500	1,750	2,350	4,200
Opening Width of Jaw	mm	0~800	0~870	0~980	0~1,120	0~1,280
Operating Pressure	bar	260	280	300	300	300
Applicable Carrier	ton	13~18	20~22	22~25	28~37	42~47

※The above specifications are subject to change without prior notice for improvement.



• Shear

Model	Unit	SDS 400RV	SDS 500RV	SDS 600RV	SDS 700RV
Operating Weight	kg	1,800	2,200	3,100	6,000
Opening Width of Jaw	mm	0~400	0~500	0~700	0~900
Operating Pressure	bar	260	300	320	320
Applicable Carrier	ton	13~18	18~25	28~37	42~47

※The above specifications are subject to change without prior notice for improvement.

